

#### FAB6 & FAB8 SERIES FULLY AUTOMATIC ROTARY BLISTER SEALING MACHINES



Line

FAB6-1418

FAB8-1418

(Heritalipale)

## EXPERIENCE the STARVIEW ADVANTAGE

Indonesia Sales and Distributing by :





#### FAB6 & FAB8 SERIES FULLY AUTOMATIC ROTARY BLISTER SEALING MACHINES

#### YOUR MARKET ... OUR SOLUTIONS

Starview's **FAB Series** fully automated rotary type blister sealing machines are ideal for high volume or JIT production. Given the proper conditions certain models of these machines are capable of up to 20 cycles per minute in production. The **FAB Series** automated rotary blister sealing machines are built with the capability to feed blister(s), blister card(s) and discharge finished packages when proper tooling is installed. These machines may be used for conventional carded blisters, trapped blisters, club store trapped packages, full face blisters and half-clamshell styles as well as some applications using Tyvek, foils and other heat sealable lidstock. Four (4), six (6) and eight (8) station models are available. Four station models have 10" x 12" and 12" x 16" sealing areas and six and eight station machines are available with 14" x 18" or 18" x 24" sealing areas.

For machines capable of higher finished package volumes or with additional open stations for automation please consider Starview's **BSC Series Carousel** or **CBS Series Inline machines.** 

# the **STARVIEW ADVANTAGE**



- A wide range of standard and custom automation features available to match customer requirements.
- ANSI Class 4 machine safety for operator protection.
- Automatic blister feeder, card feeder & finished package unloader provide reduced labor costs.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- AC Variable frequency precision cam index rotary table drive for smooth table operation and position repeatability.
- Quick-change mounting for relieved face plates
- Ses quick-change cost effective multi-ply hardwood or durable aluminum tooling.
- Industry leading design, construction, features and customer support.



more on next page



(1) Standard

(2) Standard

Standard

3.5″

1-16 cpm

208-230 Volts / 3 PH / 45 Amps

### FAB6 & FAB8 SERIES SPECIFICATIONS

Blister feeder:

Card feeder(s):

Electrical:

Finished package unloader:

Maximum blister depth:

Average cycle speed:

	FAB6-1418	FAB6-1824	FAB8-1418
Nominal sealing area:	14″ x 18″	18″ x 24″	14″ x 18″
Open loading stations:	2	2	4
Blister feeder:	(1) Standard	(1) Standard	(1) Standard
Card feeder(s):	(1) Standard	(1) Standard	(1) Standard
Finished package unloader:	Standard	Standard	Standard
Maximum blister depth:	3.5″	3.5″	3.5″
Average cycle speed:	1 – 18 cpm	1 — 14 cpm	1 — 18 cpm
Electrical:	208-230 Volts / 3 PH / 25 Amps	208-230 Volts / 3 PH / 45 Amps	208-230 Volts / 3 PH / 25 Amps
	FAB8-1418-3	FAB8-1824	FAB8-1824-3
Nominal sealing area:	14" x 18"	18″ x 24″	18″ x 24″
Open loading stations:	3	4	3

Specifications and model availability are subject to change without notice

(1) Standard

(1) Standard

Standard

3.5″

1 – 16 cpm

208-230 Volts / 3 PH / 45 Amps

MEMBER



(1) Standard

(2) Standard

Standard

3.5″

1-18 cpm

208-230 Volts / 3 PH / 25 Amps

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.

#### PT. Ecobliss Kemasindo

Jl. Prepedan Raya No. 37 Kel. Tegal Alur, Kec. Kalideres Jakarta 11820, Indonesia T +62 878 7781 3535 e-mail : info@ecobliss.co.id