



## SB, SSB SERIES GENERAL PURPOSE SHUTTLE BLISTER SEALING MACHINE



ESB1-1012



SB1-1418



SB1-1012

**EXPERIENCE**  
*the* **STARVIEW**  
**ADVANTAGE**  
INNOVATIVE PACKAGING MACHINES

Indonesia Sales and Distributing by :



# SB, ESB & SSB SERIES GENERAL PURPOSE SHUTTLE BLISTER SEALING MACHINE

## YOUR MARKET ... OUR SOLUTIONS

The **SB** and **SSB Series** Manual Shuttle Blister Sealers are designed and built for industrial applications.

These machines are simply designed for ease of operator training and operation.

An efficient heating system keeps power consumption low. This series machines can adapt to seal blister packages for a wide range of products by simply changing the tooling. These systems are competitively priced making them ideal for contract packagers or low volume equipment manufacturers. The **SB** and **SSB Series** shuttle sealers will provide years of dependable performance with a minimum of maintenance.

For machines capable of higher production rates please consider Starview's **RB, ERB, FAB, BSC & CBS Series**.



SSB2-1418

## the **STARVIEW** **ADVANTAGE**

- A heavy-duty industrial unit that can produce packages that look like they were produced on a high production machine.
- Uses quick-change cost effective multi-ply hardwood or durable aluminum tooling.
- Large sealing area MS Series machines available to produce oversize packages such as club store trapped blister designs.
- Digital temperature controller and electronic sealing cycle timer for process repeatability.
- Industry leading design, construction, features and customer support.
- 
- 
- 



Markets we serve everyday

more on next page

# SB, ESB & SSB SERIES SPECIFICATIONS

	SB1-1012	SB1-1418
Nominal sealing area:	10" x 12"	14" x 18"
Number of open stations:	1	1
Floor stand:	N/A	Standard
Max blister depth:	3.25"	3.25"
Average cycle speed:	1 – 6 cpm	1 – 6 cpm
Electrical:	115 Volts / 1 PH / 13 Amps	208-240 Volts / 1 PH / 13 Amps

	ESB1-1012	SSB2-1418
Nominal sealing area:	10" x 12"	14" x 18"
Number of open stations:	1	2
Floor stand:	N/A	Standard
Max blister depth:	3.25"	3.25"
Average cycle speed:	1 – 6 cpm	1 – 6 cpm
Electrical:	115 Volts / 1 PH / 15 Amps	208-240 Volts / 1 PH / 13 Amps

*Specifications and model availability are subject to change without notice.*



REQUEST  
A  
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



**PT. Ecobliss Kemasindo**  
 Jl. Prepedan Raya No. 37  
 Kel. Tegal Alur, Kec. Kalideres  
 Jakarta 11820, Indonesia  
 T +62 878 7781 3535  
 e-mail : info@ecobliss.co.id