

ERB6-1418

ERB SERIES SEMI-AUTOMATIC ROTARY BLISTER SEALING MACHINES

ERB6-1824 SHOWN WITH OPTIONNAL SELF STANDING CARD FEEDER AND SELF STANDING FINISHED PACKAGE UNLOADER

EXPERIENCE the STARVIEW ADVANTAGE

Indonesia Sales and Distributing by :





ERB SERIES SEMI-AUTOMATIC ROTARY BLISTER SEALING MACHINE

YOUR MARKET ... OUR SOLUTIONS

Starview's ERB series rotary type heat sealers are designed for medium to higher volume production requirements. These machines may be used for conventional carded blisters, trapped blister, club store trapped packages, full face blisters and half-clamshell styles as well as applications using Tyvek, foils and other heat sealable lidstock. The **ERB serie** units are available in six (6) and eight (8) station designs. Models are available in standard sealing areas of 14 x 18 and 18 x 24 inches. Larger sealing areas are available on request. The standard machines feature one sealing station with the remaining stations used for load/unload stations.

For machines capable of higher production rates please consider Starview's FAB, BSC & CBS Series.

the **STARVIEW ADVANTAGE**



- A wide range of standard and custom features available to match customer requirements.
- ANSI Class 4 machine safety for operator protection.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- Uses quick-change cost effective multi-ply hardwood or durable aluminum tooling.
- AC Variable frequency precision cam index rotary table drive for smooth table operation and position repeatability.
- Starview's exclusive selectable sealing station program allows the use of one (1) through six (6) sealing fixtures with operator selected start position from the HMI for short runs or single person operation.
- Optional self-standing card feeder and Anished package unloader may be added at any time to increase the machine versatility and lower labor costs.
- Industry leading design, construction, features and customer support.



more on next page



ERB SERIES — SPECIFICATIONS

	ERB6-1418	ERB6-1824
Nominal sealing area:	14" x 18"	18″ x 24″
Number of open stations:	5	5
Maximum blister depth:	3.25″	3.25″
Average cycle speed:	1 – 15 cpm	1 — 15 cpm
Electrical:	208-230 Volts / 1 PH / 25 Amps	208-230 Volts / 1 PH / 55 Amps or 208-230 Volts / 3 PH / 40 Amps

	ERB8-1418	ERB8-1824
Nominal sealing area:	14"x 18"	18″ x 24″
Number of open stations:	7	7
Maximum blister depth:	3.25″	3.25″
Average cycle speed:	1 – 15 cpm	1 – 15 cpm
Electrical:	208-230 Volts / 1 PH / 30 Amps or 208-230 Volts / 3 PH / 20 Amps	208-230 Volts / 1 PH / 63 Amps or 208-230 Volts / 3 PH / 40 Amps

Specifications and model availability are subject to change without notice.

REQUEST

A QUOTE

MEMBER

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.

TANY EW

PT. Ecobliss Kemasindo

Jl. Prepedan Raya No. 37 Kel. Tegal Alur, Kec. Kalideres Jakarta 11820, Indonesia T +62 878 7781 3535 e-mail : info@ecobliss.co.id